



EtherHaul™-1200T-L

The EtherHaul-1200T-L product provides wireless point-to-point 700Mbps (half duplex) Ethernet connectivity. It is designed to meet the growing need of carriers and businesses for secure and reliable high-capacity network connectivity.

Based on Siklu's revolutionary integrated-silicon technology, EtherHaul-1200T-L provides a high performance E-band radio solution that is reliable, small, light-weight and easy to install.

EtherHaul-1200T-L offers high throughput, MEF-compliant networking and QoS. The product features enhanced Hitless Adaptive Bandwidth, Coding & Modulation for maximum spectral efficiency, and link availability.


Typical Applications

Business services connectivity	<ul style="list-style-type: none"> ✓ Leased line replacement ✓ LAN and fiber extension
LAN to LAN connectivity	High capacity and secure connectivity <ul style="list-style-type: none"> ✓ Healthcare ✓ Education ✓ Security ✓ Disaster recovery
Temporary network deployments	
Redundant connectivity	



Features & Benefits

- **Field proven technology and products**
- **High performance**
 - ✓ High throughput, low latency
 - ✓ Fiber-like functionality
- **Spectrum efficient**
 - ✓ Uncongested, inexpensive Eband license fees
 - ✓ Hitless Adaptive Bandwidth Coding and Modulation for high availability
 - ✓ High-gain, pencil-beam antenna
- **All-outdoor small footprint**
 - ✓ Small and light
 - ✓ Quick and easy to install
- **Reduced TCO and fast ROI**
- **Advanced AES encryption**
 - ✓ Secured transmission
- **Integrated Silicon solution**



EH1200T-L Technical specifications

Interfaces	<ul style="list-style-type: none"> Ethernet : 2 combo ports - 100/1000Base-T (RJ45) + 2 x 1000Base-X (SFP) AUX port - DVM probe interface for alignment
System throughput	<ul style="list-style-type: none"> 700Mbps half-duplex
Radio	<ul style="list-style-type: none"> Operating Frequency Range - 71-76 GHz Duplexing- TDD Modulation Schemes- QPSK-4 to QAM 16 RF Channel Arrangement- <ul style="list-style-type: none"> 500 MHz: 71375 + n x 500 MHz, n=0...8 250 MHz: 71250 + n x 250 MHz, n=0...18 Hitless adaptive bandwidth, coding and modulation, boosting system gain by 25dB
System Gain	<ul style="list-style-type: none"> 182dB (including 1ft antennas gain) 196dB (including 2ft antennas gain)
Antenna	<ul style="list-style-type: none"> Integrated 1ft (31cm) Cassegrain reflector <ul style="list-style-type: none"> 43dBi antenna gain External 2ft (65cm) Cassegrain reflector <ul style="list-style-type: none"> 50dBi antenna gain
Power specifications	<ul style="list-style-type: none"> Standard Input - -48 VDC, -24 VDC DC Input wide Range - -21 ÷ -57 VDC Power over Ethernet Input - IEEE 802.3at-2009 Power redundancy - PoE and power input redundancy
Ethernet features	<ul style="list-style-type: none"> VLAN (IEEE 802.1q) and VLAN stacking (Q-in-Q, IEEE 802.1ad Provider Bridge) IEEE 802.1d Transparent Bridging QoS, traffic shaping, and policing MEF 9,14 and 21 compliant
Security	<ul style="list-style-type: none"> AES 128-bit and 256-bit
Management	<ul style="list-style-type: none"> Out of band , Inband management via Vlan, CLI/Telnet via SSH Embedded WEB GUI LLDP- 802.1AB SNMPv2/3
Conformance	<ul style="list-style-type: none"> CE marked RF: EN 302 217-3 1.3.1 EMC- EN 301 489-4 Safety - UL60950
Environmental characteristic	<ul style="list-style-type: none"> Operating Temperature- -45° ÷ +55° C Ingress Protection Rating - IP67
Mechanical	<ul style="list-style-type: none"> Dimensions: <ul style="list-style-type: none"> ODU (H x W x D): 24.5 cm x 22.5 cm x 7 cm ODU + Antenna - 31 cm (Dia. x Depth): 31 cm x 13 cm Weight : <ul style="list-style-type: none"> ODU: 2.5 kg ODU + antenna (31 cm): 4 kg



Contact information

e-NETSource
 PO Box 402 Chatswood NSW 2057
 Australia
 Tel: +61 (0)2 800 373 27
 Fax: +61 (0)2 800 704 37
 sales@e-netsource.com

The Siklu logo and EtherHaul™ are trademarks of Siklu Communication Ltd. This brochure is for information purposes only. The details contained in this document, including product and feature specifications, are subject to change without notice. This brochure shall not bind Siklu to provide to anyone a specific product or set of features related thereto.



www.e-NETSource.com